

## INTERCONNECTING PRODUCTS AND CABLES

# I-7000

## RS-485 Data Acquisition and Control Modules

- Distributed Data Acquisition and Control Modules.  
*Control and Data Acquisition where you need it, as you need it.*
- Standard baud rates up to 115.2 kbaud.  
*Handles the highest speed serial devices.*
- 3000 V Isolation  
*Reduces noise, no ground loops.*
- Read Analog Signals, temperatures or digital inputs. Control with analog outputs or contact closures.  
*Select the I/O Modules for your application.*
- Mounts on standard DIN rail.  
*Easy mounting and replacement.*
- Easy network control with Setup Wizard and VxComm driver.  
*Sets IP Address and Assigns devices to a virtual COM port.*

**CE** Approved

### Description

The I-7000 Series is a family of Data Acquisition and Control Modules that gives the user an easy way to build a distributed Data Acquisition or Control system. All modules are controlled over an RS-485 network at rates up to 115,200 baud. The Model I-7017 has 8 analog input channels and the Model I-7018 has 8 thermocouple input channels. The Model 7024 has 8 analog output channels. The Model I-7060 has 4 digital inputs and 4 sets of relay contacts and 4 sets of relay contacts. All units are designed for industrial applications, have 3000 V isolation to the RS-485 network for noise free operation, dual watchdog timers and fail safe outputs.

### RS-485 Communication

The I-7000 series modules are controlled over an RS-485 network. RS-485 networks use differential signals and have a high degree of noise immunity due to the differential nature. Cable lengths can be up to 4,000 feet. The I-7000 communication protocol uses command packets with an address character and a checksum to validate the packet. All packets are acknowledged and erroneous packets are resent. The module address can be 01 to 255. All module configuration parameters such as address, baud rate etc. are saved in an internal EEPROM. D units have an optional 5 digit LED display.



**I-7017 Analog Module**

### I-7017

The I-7017's 24-bit sigma-delta A/D converter reads 8 channels at a 10 channel per second rate. Input ranges can be set to +10 V, +5 V, +1 V, +500 mV, +150 mV and 0 to 20 mA. The I-7017F has the same specifications but has a faster 75 samples per second sampling rate.

### I-7018

The I-7018's 24-bit sigma-delta A/D converter reads 8 channels of voltage or thermocouple inputs. The module has a Cold Junction Compensation circuit and can handle virtually any type of thermocouple. Temperature range depends upon the thermocouple. Voltage input ranges are from +2.5 V, +1 V, + 500 mV, +100 mV, +50 mV and +15 mV. The I-7018P has the same specifications but handles two additional thermocouple types.

### Popular I-7000 Configurations

Model	Description	Display
I-7017	8 ch diff Analog Input, mV/V, 10 s/sec	None
I-7017F	8 ch diff Analog Input, mV/V, 75 s/sec	None
I-7018	8 ch diff Analog Input, mV/V/thermocouple, 10 s/sec	None
I-7019	8 ch diff Analog Input, mV/V/20mA/thermocouple	None
I-7024	4 ch D/A 12-bit, 4-20 mA or 0-10 Vdc.	None
I-7060	4 digital inputs, 4 sets of relay contacts	None

## I-7019

The I-7019 is a Universal Analog Input Module that can handle voltage, millivolt and thermocouple inputs. The I-7019 has 8 differential analog inputs with nine DC voltage ranges from  $\pm 15$  mV to  $\pm 10$  V. Also reads  $\pm 20$  mA current. Resolution is 16-bits with an accuracy of  $\pm 0.1\%$ . Channels are individually configurable. The I-7019 also handles most commercial thermocouples and includes a wire open detection logic. The thermocouple types are: J, K, T, E, R, S, B, N, C, L, M and L2. The following chart lists the thermocouple types and their temperature ranges.

Type	Code	Temperature Range °C
J	0E	-210 to +760
K	0F	-270 to +1372
T	10	-270 to +400
E	11	-270 to +1000
R	12	0 to +1768
S	13	0 to +1768
B	14	0 to +1820
N	15	-270 to +1300
C	16	0 to +2320
L	17	-200 to +800
M	18	-200 to +100
L2	19	-200 to +900

Note: L2 is DIN 43710

## I-7024

The I-7024 provides 4 analog outputs that can provide  $\pm 10$  V,  $\pm 5$  V, 5 V, 10 V, 4 to 20 mA or 0 to 20 mA. Power on settings can be stored in the module's internal EEPROM.

## I-7060


The I-7060 provides four isolated digital inputs and four relay outputs. The digital inputs have a wide range of voltage inputs. Logic 0 is 0 to +1 volt. Logic 1 is +3.5 to +30 volts. The four sets of relay contacts are two SPST (Form A) contacts and two SPDT (Form C) contacts. Both contact types are shown in the figure on the right. Contact ratings are a rugged 2 A at 30 VDC and 0.5 A at 115 VAC.

## I-7060D

The I-7060D adds 8 LEDs to the standard I-7060 as shown in the photo on the right. The I-7060D provides four isolated digital inputs and four relay outputs. The digital inputs have a wide range of voltage inputs. Logic 0 is 0 to +1 volt. Logic 1 is +3.5 to +30 volts. Digital input #4 can be used as a 16 bit counter with rates up to 100 kHz. The four sets of relay contacts are two SPST (Form A) contacts and two SPDT (Form C) contacts. Contact ratings are a rugged 2 A at 30 VDC and 0.5 A at 115 VAC. The I-7060D LEDs show which relays are energized.



I-7060 Isolated Digital Input and Relay Module



I-7060 Form A and Form C Contacts

## Operation

INIT pin - Enables setting the module configuration parameters.

Power on Values - Set at power on or when Watchdog reset occurs.

Optional Display - Show the status of the module, its IP address and serial port configuration settings. Models with the display are noted with a D after the part number.

## Serial Interface

RS-485 Interface is half-duplex. Protocol includes address and checksum.

Signals	TX/RX pair
Baud Rates	Std Windows rates up to 115.2 kbaud.
Data Bits	7 or 8 bits
Parity	None, odd, or even
Stop bits	1 or 2
Distance	1200 M



I-7060 Isolated Digital Input and Relay Module with Display LEDs

## I-7000 SPECIFICATIONS

### I-7017 Specifications

Channels	8 diff or 6 diff/2 SE
Input Ranges	±150 mV, ±500 mV, ±1 V, ±5 V, ±10 V and ±20 mA
Rate	10 samples/sec
Resolution	16-bit
Accuracy	± 0.1%
Zero drift	± 0.03µV/°C
Span drift	25ppm/°C
CMR	92 dB @50/60 Hz
Overvoltage	± 35V
I-7017F same specifications at 10 samples/sec. Changes are:	
Rate	75 samples/sec
Accuracy	± 0.5%

### I-7018 Specifications

Channels	8 diff or 6 diff/2 SE
Input Ranges	±15 mV, ±50 mV, ±100 mV, ±1 V, ±2.5 V and ±20 mA
Rate	10 samples/sec
Resolution	16-bit
Accuracy	± 0.05%
Zero drift	± 0.03µV/°C
Span drift	25ppm/°C
CMR	150 dB @50/60 Hz
NMR	150 dB @50/60 Hz
Overvoltage	± 35V
thermocouples	J, K, T, E, R, S, B, N, C (L and M -7018P only)

### I-7018 Specifications

Channels	8 differential
Input Ranges	±15 mV, ±50 mV, ±100 mV, ±1 V, ±2.5 V ±5 V, ±10 V and ±20mA
Input Imp.	20 Mohm for voltage
Resolution	16-bit
Accuracy	± 0.1%
CMR	86 dB @50/60 Hz

### I-7024 Specifications

Channels	4
Output Ranges	0-20 mA, 4-20 mA, 5 V, 10 V and ±10 V
Resolution	14-bit
Accuracy	± 0.1% FSR
Readback	± 1 % FSR
Zero drift	± 0.153µV/°C ± 0.2 µA/°C
Prog slope	0.0625 to 64 V/sec 0.125 to 125 mA/sec
Load	5 mA

### I-7060 Specifications

Relays	4
Contact type	2 SPST 2 SPDT
Contacts	125VAC @0.6A; 250VAC @0.3A 30VDC @2A; 110VDC @0.6A
Breakdown V	500 VAC at 50/60 Hz
Relay On Time	3 ms typ
Relay Off Time	1 ms typ.
Digital inputs	4
Logic 0	0 to +1 VDC
Logic 1	+3.5 to +30 VDC
Isolation	3750 V
Input Imp.	3 kohm

### Physical

Size	123mm x 72mm x 33 mm (without mounting bracket)
Mounting	DIN rail
Display (optional)	5 digit LED display or single LED
Connectors	Serial Screw terminals for 16 to 26 AWG wires, 0.15 in centers
Temperature	Operating -25 °C to 75 °C Storage -40 °C to 85 °C
Relative humidity	0 to 90% (not condensing)
Power consumption	1.3 W @ 10 to 30 Vdc (7017/18/19/ and 60) 2.2 W @ 10 to 30 Vdc (7024)

### CE Certification

EMC Directive	89/336/EMC
Emission	EN 55022
Noise immunity	EN 50082-2C

### Included Items

Single unit	DIN rail
Manual	on CD-ROM
UL/CSA/VDE approved	AC power Adapters provided for:
US	- 115±10% Vac, 60 Hz (std)
Europe	- 230±10% Vac, 50/60 Hz
UK	- 230±10% Vac, 60 Hz

## ORDERING INFORMATION

	Part Number
Input Module with 8 channels A/D, 3000 V Isolation	I-7017
Input Module with 8 channels fast A/D, 3000 V Isolation	I-7017F
Input Module with 8 channels A/D for thermocouples, 3000 V Isolation	I-7018
Input Module with 8 channels A/D for voltage and thermocouples, 3000 V Isolation	I-7019
Output Module with 4 channels analog output, 3000 V Isolation	I-7024
Control Module with 4 sets of relay contacts and 4 isolated digital inputs	I-7060

For units with optional LED display add 'D' suffix. i.e. 7060 becomes 7060D.

For 230 VAC adapter, add suffix to specify country / plug style) -E(Europe), -B(UK), -A(Australia) i.e. I-7188E2-B